



АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ

ELEMENTRAC CS-d

ELTRA's ELEMENTRAC CS-d is the only analyzer in the market for determination of carbon and sulfur in organic as well as inorganic samples. For this purpose, the ELEMENTRAC CS-d is equipped with both an

induction and a resistance furnace (ELTRA Dual Furnace Technology), covering the full range of carbon and sulfur analysis.

Up to four highly sensitive infrared (IR) cells allow for precise measurement of both high and low carbon and sulfur concentrations in only one analysis. The measuring range of each cell may be adapted to the user's specific requirements to ensure optimum measurement conditions for each application.

The ELEMENTRAC CS-d is supplied with the comprehensive and user-friendly ELEMENTS software.



[Смотреть видео](#)

Видео о приборе

FULL FLEXIBILITY WITH TWO FURNACES

- | Full flexibility due to combined induction and resistance furnace: ELTRA Dual Furnace (EDF) Technology
- | Rapid and accurate carbon & sulfur analysis in inorganic and organic samples
- | Up to four independent infrared cells with flexible measuring ranges
- | Gold IR path allows for increased cell lifetime for analysis of halogen- or acid-containing samples
- | Simultaneous carbon and sulfur determination with minimum sample preparation
- | Robust design allows usage in production control and laboratory




АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ ELEMENTRAC CS-D

OPERATION AND ANALYSIS PROCESS

Operation of the ELEMENTRAC CS-d is easy and convenient and only requires a few steps. The typical sample weight for carbon / sulfur analysis is about 50 to 1000 mg. This is sufficient to reliably detect concentrations from 1 ppm to 100%. Before the combustion process it is necessary to extract a sample from the initial amount which strongly varies, depending on the matrix. International standards like DIN EN ISO 14284 (Sampling of steel and iron) give some orientation.

INDUCTION FURNACE



Step 1: Logging the sample into the ELEMENTS software

The sample ID is logged into the software and the weight is automatically transferred (see step 2).



Step 2: Weighing and adding of accelerators

Sample volumes of 50 mg to 1000 mg are typical for C/S analysis. The sample is weighed in a ceramic crucible and accelerators like tungsten are added. The geometry of the sample (e. g. wire, powder, pin etc.) is not essential for a reliable analysis.



Step 3: Analysis


The ceramic crucible is then placed on the pedestal of the CS-d and the analysis is started via the ELEMENTS software. The software controls all subsequent steps like combustion and evaluation.



Step 4: Data output and export

45-60 seconds after the analysis has started, the measured carbon and sulfur concentrations are available for export as a report or via LIMS.

RESISTANCE FURNACE



Step 1: Logging the sample into the ELEMENTS software

The sample ID is logged into the software and the weight is automatically transferred (see step 2).



Step 2: Weighing of the sample

Volumes of 50 mg to 500 mg are typical for C/S analysis in a resistance furnace. The sample is directly applied to a boat. Accelerators are usually not required.



Step 3: Analysis

The sample is placed in front of the furnace and the measurement is started in the software. A green LED signals when the sample can be introduced. During combustion the ELEMENTS software continuously records measurement values.



Step 4: Data output and export

60 to 240 seconds after the analysis has started, the measured carbon and sulfur concentrations are available for export as a report or via LIMS.


АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ ELEMENTRAC CS-D

CONFIGURATIONS

The ELEMENTRAC CS-d is available as a single-element analyzer for carbon or sulfur only, or in a configuration for simultaneous measurement of both carbon and sulfur. It uses up to four IR cells for this purpose which can be adapted to individual requirements. As the length of the cuvette increases, so does the sensitivity for low concentrations (e. g. 10 ppm). Shorter cells can still measure samples with low levels in the ppm range, but the standard deviation of the measured values increases significantly. For optimum measurement of low and high concentrations, it is therefore recommended to use two IR cells per element. The latest detector technology enables a wide measuring range for carbon and sulfur from the ppm range up to 100 % in both induction and resistance furnace. In addition, gold cuvettes installed as standard offer greater reliability for elemental analysis of samples containing halogens.

A special option for the ELEMENTRAC CS-d is a halogen trap to reliably bind even very high halogen concentrations. The carbon / sulfur analyzer can also be delivered in a special configuration for the analysis of cement.

Infrared cells with flexible measuring range



АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ ELEMENTRAC CS-D

INTEGRATED STANDARD SOLUTIONS

The ELEMENTRAC CS-d offers intelligent solutions as standard features to provide accurate and reliable measurement of the carbon and sulfur concentrations also in complex sample:

Intelligent Lance Management

Due to the high temperatures in the induction furnace of >2000 °C and the high oxygen flow of 180 L/hour, solid samples of all types are completely decomposed, allowing for determination of the C/S content with the aid of infrared measuring cells. Here, thorough combustion ensures reliable measurement results.

Since powder samples might splash out of the crucible, which could lead to results below the actual value, the CS-d features an intelligent lance and combustion management system to ensure complete combustion without sample loss.

For this purpose, the oxygen flow to be dosed can be applied via a lance or the chamber to prevent blowing of the sample and allowing for controlled combustion. The ramping function of the induction furnace enables a gentle combustion process by gradual power increase.



Sample port in the resistance furnace (blank value reduction)

The ELEMENTRAC CS-d provides accurate and reliable analysis of samples with a low carbon content in the resistance furnace. Thanks to the optimized sample port geometry with reduced diameter and oxygen flushing at the sample entrance, the CO₂ blank value of the atmosphere is drastically reduced when the sample is introduced which allows for reliable results in the low measuring range.



АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ ELEMENTRAC CS-D

OPTIONS

In addition to the integrated features of the ELEMENTRAC CS-d, further options are available to increase the efficiency of the carbon / sulfur measurement.


AUTOLOADER

The induction furnace of the ELEMENTRAC CS-d can be equipped with an optional automatic sample loader. The standard module offers 36 crucible positions, the XL model even features 130 positions. It is the largest Autoloader available in the market for this type of application.



[Смотреть видео](#)







TIC MODULE


Carbon can be determined as total carbon (TC) or in fractions, i. e. total organic carbon (TOC) or total inorganic carbon (TIC). When combined with the CS-d, ELTRA's TIC module measures the TIC content (e. g. lime) by acidification in products like soil or construction materials.



IOT - INTERNET OF THINGS

THE PLATFORM FOR REMOTE ACCESS TO YOUR DEVICES

All ELTRA analyzers seamlessly integrate with the Verder Scientific IoT platform, providing enhanced functionality, seamless connectivity, and additional benefits:



- | **Real-time Monitoring:** Gain insight into the status of your machines at any time thanks to immediate access to important data.
- | **Live Notifications:** Stay up to date on the status of your devices with instant notifications.
- | **Effortless Backup:** Whether you need to back up a single device or an entire fleet, back up your data effortlessly and minimize downtime.
- | **Automatic Software Updates:** Verder Scientific IoT keeps your device software up to date, optimizing performance and reliability.
- | **Access to Analyses Data:** ELTRA analyzers offer remote access to analysis data. This allows you to conveniently access important data while on the move.
- | **Autoloader Efficiency:** Get the most out of remote analysis preparation with our autoloader feature, which ensures uninterrupted operation and increased productivity for all instruments equipped with it.

Experience the power of the Verder Scientific IoT platform today and unlock the full potential of your ELTRA analyzers!



**FREE SOFTWARE
DOWNLOAD**

АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ ELEMENTRAC CS-D
ПРОГРАММНОЕ ОБЕСПЕЧЕНИЕ ELEMENTS

The comprehensive Windows-based ELEMENTS software is an essential part of all ELEMENTRAC generation elemental analyzers.

A central window (analysis and results) is the starting point from which all functionalities required for the daily routine are easily accessible. From here it is possible to group and export analyzed samples, or register and analyze new ones. The user may call up various subordinate functionalities like application settings, calibration, diagnosis, or status.




АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ ELEMENTRAC CS-D
ТИПИЧНЫЕ ОБРАЗЦЫ МАТЕРИАЛОВ

сплавы, зола, карбиды, чугун, цемент, керамика, coal, кокс, медь, стекло, гипс, железо, известняк, металлы, минералы, нефть, руды, растения, огнеупоры, резина, песок, почва, сталь, титан, табак, ...



coal



руды



сталь

АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ ELEMENTRAC CS-D

ПРИНЦИП РАБОТЫ

Regardless of which furnace is used in the ELEMENTRAC CS-d, the carbon and sulfur in the sample forms gaseous molecules like SO_2 and CO_2 during combustion. The released amounts of CO_2 and SO_2 are measured in up to 4 element-selective infrared cells. Usually, two IR cells are used for measuring one gas (CO_2 or SO_2) to ensure that both very low and very high concentrations are analyzed precise and correctly.

When the induction furnace of the CS-d is used, the carrier gas (oxygen) and the combustion products (CO_2 , traces of CO , and SO_2) are first led through a metallic filter to remove all solid particles. Afterwards, a tube filled with magnesium perchlorate removes traces of water. The dried combustion gas then passes up to two infrared cells for sulfur (SO_2) measurement. Afterwards, a heated catalyst (usually platinized silica) oxidizes the traces of carbon monoxide (CO) to CO_2 and the SO_2 molecules to SO_3 . The SO_3 gas is absorbed by cellulose and the CO_2 is measured in up to two element selective IR cells. Finally, the combustion gas is led to the exhaust and the ELEMENTS software calculates the resulting carbon and sulfur concentrations.

Whereas the induction furnace of the ELEMENTRAC CS-d is suitable for analyzing inorganic samples like steel, cast iron and ceramics, the resistance furnace is used for combustion of organic samples like coal, coke or soil. When a coal sample is combusted at temperatures of approx. 1350°C , CO_2 and SO_2 are released but usually no carbon monoxide (CO) is formed. The combustion gases of the



resistance furnace first pass a ceramic filter for absorption of particles, followed by a glass tube with magnesium perchlorate.

After that the dried combustion gases pass the same path as those from the induction furnace. Usually, the catalyst furnace is switched off during usage of the resistance furnace because oxidation of CO is not required.

However, the risk of incomplete combustion and formation of carbon monoxide increases at lower temperatures (~600 °C); in such cases the catalyst furnace may be switched on.

АНАЛИЗАТОР УГЛЕРОДА / СЕРЫ ELEMENTRAC CS-D

ОСОБЕННОСТИ

Измеряемые элементы	сера, углерод
Материал проб	органические и неорганические материалы
Направление ввода пробы в печь	вертикально (индукционная печь), горизонтально (печь сопротивления)
Подача пробы в печь	лодочки / тигли
Область применения	Сталелитейное производство/ Металлургия, геология / добыча ископаемых, инженерное дело / электроника, медицина / фармацевтика, окружающая среда / переработка, сельское хозяйство, стекло / керамика, строительные материалы, угольная промышленность / энергетика, химическая промышленность / пластики
Печи	индукционная печь с температурой выше 2000 °C / печь сопротивления, температура настраивается с шагом 1 °C максимум до 1550 °C
Принцип детектирования	метод инфракрасной абсорбции
Количество ИК кювет	1 - 4
Материал ИК кювет	золотые
Типичное время анализа	индукционная печь 40 - 50 с / печь сопротивления 60 - 120 с
Требуемые реактивы	гидроксид натрия, перхлорат магния, платинизированный силикагель (замена оксида меди)
Требуемый газ	сжатый воздух (4 - 6 bar) кислород чистоты 99.5 % или лучше (2 - 4 bar)
Требования к электропитанию при работе с индукционной печью	230 В, 50/60 Гц, предохранитель на 16 А
Требования к электропитанию при работе с печью сопротивления	230 В, 50/60 Гц, предохранитель на 20 А
Размеры (Ш x В x Г)	89 x 84 x 79 см
Вес	~ 200 кг
Требуемое оборудование	ПК, монитор, весы (точность 0.0001г)
Опции	Autoloader for 36 crucibles, HTF-540 pre-heating furnace, autoloader for 130 crucibles, Газ носитель, Галогеновые ловушки

www.eltra.com/cs-d

ИНФОРМАЦИЯ ДЛЯ ЗАКАЗА

ELTRA CS-D

(Пожалуйста, отдельно закажите управляющий компьютер, монитор, весы и расходные материалы)

Measuring ranges at 1000 mg sample weight (induction furnace) || 350 mg sample weight (resistance furnace) 2)
(further measuring range combinations on request)

индукционная печь || печь сопротивления

88200-1211		CS-d	2xC	0.0001 – 7 % C		0.004 – 62.8 % C
88200-1212		CS-d	2xS	0.00006 – 2.3 % S		0.001 – 31.4 % S
88200-1233		CS-d	2xC	0.0001 – 7 % C		0.004 – 62.8 % C
			2xS	0.00006 – 2.3 % S		0.001 – 31.4 % S

Every configuration can be equipped with an autoloader for the induction furnace.
No special “autoloader ready” configuration has to be purchased.

REQUIRED ACCESSORIES

УПРАВЛЯЮЩИЙ КОМПЬЮТЕР, МОНИТОР, ВЕСЫ

71015-1000 Computer with Intel Core i5-8400 Processor, 256 GB SSD; 8 GB RAM; Windows 10 operating system; keyboard; mouse

88400-0584 Monitor, TFT (23.8")

88400-0645 Весы (разрешение 0.0001 г)

REQUIRED CONSUMABLES / CHEMICALS FOR FIRST OPERATIONS

88500-0002 Стартовый набор на 1,000 анализов (500 тиглей, 2,500 г вольфрама, 908 г чистого железа, 50 г стекловаты, 50 г хлопковой ваты, 50 г кварцевой ваты, 50 многоразовых лодочек, 500 одноразовых фарфоровых лодочек, 100 г Combsolid)

90200  Ангидрон (перхлорат магния), 454 г l)

90210  Гидроксид натрия, 500 г 1)

88400-0535 Катализатор Pt/Si, 15 г

88600-0021 Copper oxide wire (0.5*2 mm), 100 g (could be used alternatively to Pt/Si catalyst) 1)

FURTHER OPTIONS AND CONSUMABLES

ACCESSORIES (HARDWARE)

72070 Редуктор кислорода

88200-9000 Carrier gas purification furnace, without filling (please order filling and quartz wool separately)

88400-0122  Filling for carrier gas purification furnace (CS)

88400-0610 Barcode scanner

88200-3800  TIC-модуль

88200-1400 Autoloader (36 positions) for induction furnace

88200-1500  Autoloader (130 positions) for induction furnace

88600-0018  CS-i vacuum cleaner (with HEPA filter)

88600-0020 Halogen trap CS-i / CS-d

CRUCIBLES AND LIDS FOR THE COMBUSTION FURNACE

90149  Керамические тигли, премиум Ø 1", завернуты в фольгу, 1,000 штук

90148  Керамические тигли, премиум Ø 1", упакованы в пакеты, 1,000 штук

88400-0176 Керамические фильтрующие тигли, 100 штук

88600-0014  Ceramic lids, 10 mm hole, 250 pieces

88600-0017 Ceramic lids, 4 mm hole, 1000 pieces

BOATS FOR THE RESISTANCE FURNACE

90153		Многоразовые керамические лодочки, премиум 58x22x14 мм, 500 штук
90160		Disposable porcelain boats, 86 x 13 x 10 mm, 1000 pieces
88600-0011		Re-usable ceramic boats, 95 x 13 x 10 mm, 500 pieces
88400-0502		Re-usable inconel boat, 54 x 18 x 13.5 mm, 1 piece
88400-0503		Re-usable inconel boat, 54 x 18 x 9 mm, 1 piece

ACCELERATORS FOR THE INDUCTION FURNACE

90220		Вольфрам, 2,500 г
90260		Акселератор Железо, 908 г
88600-0013		Акселератор железа высокой чистоты, 454 г
88600-0010		Eltracell tungsten-tin accelerator, 750 g
90280		Акселератор олово, 908 г
90240		Акселератор медь, 1392 г

COMBUSTION SUPPORT FOR THE RESISTANCE FURNACE

90840		Кварцевый песок, 100 г
88600-0008		Акселератор Combsolid, 100 г

CHEMICALS

90200		Ангидрон (перхлорат магния), 454 г l)
90210		Гидроксид натрия, 500 г l)
88400-0535		Pt/Si catalyst, 15 g
90331		Стекловата, 454 г
90340		Целлюлоза, 100 г
90341		Целлюлоза, 50 г
90330		Кварцевая вата, 50 г
92610		Tube of high vacuum grease, 35 g
88400-0122		Наполнитель для печи очистки газа-носителя
91000-1005		Медь, стружка, 25 г
88400-0508		Steel wool, 454 g
88600-0021		Copper oxide wire (0.5*2 mm), 100 g (could be used alternatively to Pt/Si catalyst)

GENERAL TOOLS AND ACCESSORIES

23110		Spatula, 1 piece, M size
23111		Spatula, 1 piece, L size
23113		Spoon, 1 piece, for dosing sample and accelerator in CS series
90145		Tongs for ceramic crucibles and boats, 220 mm 1 piece

88400-0229		Пинцет (160 мм), скругленный, 1 штука
88400-0472		Пинцет (145 мм), прямой, 1 штука
88400-0475		Набор из 6 шпателей и 1 пинцета для взвешивания проб
88400-0476		Micro spatula, 1 piece, XS size, for filling small capsules

TOOLS FOR STORAGE, TRANSPORTING AND WEIGHING

36121		Quartz boat, 74 x 22 x 10 mm, 1 piece, for weighing pins
71010		Brush, 16 mm, 1 piece, for cleaning balance from dust
88400-0477		Weighing boat, 1 piece, for weighing and usage of granulates
88600-0015		Подставка тигля, for storage of crucibles

TOOLS FOR MAINTENANCE

51200-8000		Maintenance kit CS-d
88400-0473		Powder funnel (plastics), 1 piece, for easy filling of chemical tubes
88400-0489		Rubber plug 14 x 20 x 24 mm, 1 piece, for sealing small glass tubes like 88400-0006
88400-0490		Rubber plug 29 x 35 x 30 mm, 1 piece, for sealing big glass tubes like 09090
88600-0026		Anhydrone filter tube
88600-0027		Sodium hydroxide, Anhydrone filter tube

TOOLS FOR CS ANALYZERS

36216-2001	Combustion boat insertion stick, 1 piece (only for CS-d)
36218-2001	Combustion boat removing stick, 1 piece (only for CS-d)

88400-0332		Threaded rod M4x150, 1 piece, for removing paper filter holder
88400-0499		Safety glasses, 1 piece, protection when working with hot furnace
88600-0009		Screen glass with edge guard, 1 piece, protection when working with hot furnace

CALIBRATION MATERIALS

Calibration materials may show slight variations depending on the current lot.

To see the current certification please visit www.ELTRA.com.

STEEL AND CAST IRON

92400-3020		Steel, 150 g, 0.001 – 0.01 % C Details
92400-3030		Steel, 150 g, 0.01 – 0.05 % C Details
92400-3050		Steel, 150 g, 0.1 – 0.2 % C Details
92400-3060		Steel, 150 g, 0.2 – 0.5 % C Details
92400-3061		Steel, 150 g, 0.2 – 0.5 % C Details
92400-3062		Steel, 150 g, 0.2 – 0.5 % C Details
92400-3070		Steel, 150 g, 0.5 – 1.0 % C Details
92400-3090		Cast iron, 150 g, 2.0 – 3.0 % C Details
92400-3091		Cast iron, 150 g, 2.0 – 3.0 % C Details
92400-3100		Cast iron, 150 g, 3.0 – 5.0 % C Details
92400-3101		Cast iron, 150 g, 3.0 – 5.0 % C Details
92400-3102		Cast iron, 150 g, 3.0 – 5.0 % C Details
92400-4005		Steel, 150 g, ~0.05 % S Details
92400-4010		Steel, 150 g, ~0.1 % S Details
92400-4020		Steel, 150 g, ~3 % S Details

STEEL PINS		DETAILS
------------	--	---------

92500-1001	C/S pins, 454 g, ~0.2 %~C Details
92500-1002	C/S pins, 454 g, ~0.4 %~C Details
92500-1003	C/S pins, 454 g, ~0.8 %~C Details
92500-2001	C/S pins, 454 g, ~0.2 % S Details

TUNGSTEN CARBIDE	
------------------	--

90816-3001	 Карбид вольфрама, 100 г, ~6,1 % C
------------	---

OTHER CALIBRATION MATERIAL SUITABLE FOR RESISTANCE AND INDUCTION FURNACE	
--	--

90812-3001	 Известняк, 25 г, 0.04 % S
------------	--

90812-3002	 Известняк, 25 г, 0.4 % S
------------	--

90812-3003	Известняк, 25 г, < 5 % C
------------	--------------------------

90812-3004	Известняк, 25 г, 5 – 10 % C
------------	-----------------------------

90817-3001	Soil, 25 g, > 2 % C, S
------------	------------------------

90817-3002	Soil, 25 g, < 1 % C, S
------------	------------------------

90817-3003	Soil, 25 g, > 2 % C, S
------------	------------------------

90817-3004	Soil, 25 g, < 2 % C, < 1 % S
------------	------------------------------

91900-1001	 Руда, 30 г, ~1.4 % S
------------	--

91900-1002	 Руда, 30 г, ~4.2 % S
------------	--

91900-1003	Руда, 30 г, ~3 % S
------------	--------------------

91900-2001	Zinc sulfide, 50 g, 32 % S
------------	----------------------------

90810	 Карбонат кальция, 100 г
-------	---

90821	 Сульфат бария, 50 г
-------	---

OTHER CALIBRATION MATERIAL ONLY SUITABLE FOR RESISTANCE FURNACE

90710-3010  ЭДТА, 50 г

90710-3030 Sucrose, 50 g

90824  Сульфаниловая кислота, 50 г

92511-3005 Уголь, 50 г, < 0.1 % S

92511-3010  Уголь, 50 г, 0.1 – 0.5 % S

92511-3020  Уголь, 50 г, 0.5 – 1.0 % S

92511-3030  Уголь, 50 г, 1.0 – 1.5 % S

92511-3040  Уголь, 50 г, 1.5 – 2.0 % S

92511-3050  Уголь, 50 г, 2.0 – 3.0 % S

92511-3060  Уголь, 50 г, 3.0 – 4.0 % S

92511-3070  Уголь, 50 г, 4.0 – 5.0 % S

92511-3080  Уголь, 50 г, >5.0 % S

COAL, PREMIUM, C/H/N/S, ASH, VOLATILE CONTENT, CERTIFIED

92550-3010 Уголь, премиум, 50 г, < 1.0 % S

92550-3020  Уголь, премиум, 50 г, > 1 % S

92550-3040  Уголь, премиум, 50 г, 1.0 – 3.0 % S

92550-3060  Уголь, премиум, 50 г, > 3.0 % S

COKE, PREMIUM, C/H/N/S, ASH, VOLATILE CONTENT, CERTIFIED

92560-3010



Кокс, премиум, 50 г

PET COKE, PREMIUM, C/H/N/S, ASH, VOLATILE CONTENT CERTIFIED

92570-3020

Pet coke, premium, 50 g, > 1 % S

92570-3040

Pet coke, premium, 50 g, > 1 % S

SPARE AND WEAR PARTS ELTRA CS-D

FRONT SIDE INDUCTION FURNACE

11093

Filter plate, 1 piece

11105



Металлический фильтр пыли

11120



Paper filter holder

11170



Фильтр тонкой очистки

11185



Paper filter (set of 10)

27000-3070

Cover furnace illumination

51100-2035

Heated dust filter cartridge

51100-2040

Dust trap connection

51200-8000

Maintenance kit CS-d

70230

O-ring 9 x 3 mm

88400-0005

Reagent tube

88400-0006



Reagent tube

88400-0332



Threaded rod M4 x 150, 1 piece

INDUCTION FURNACE OF CS-D

14021		Complete top furnace locking device
14045		Щетка чистки печи
14051		Brush holder
14072		Керамическая защита
14130		Трубка сгорания
14168		Пьедестал
70120		O-ring 3.4 x 1.9
70380		O-ring 35 x 5 mm (2 pieces required for combustion tube)
70390		O-ring 38 x 5 mm
		Catalyst furnace
66500-0084		Hose clip
70180		O-ring 8 x 1.5 mm for catalyst furnace
70200		Уплотнительное кольцо
70230		O-ring 9 x 3 mm
88400-0422		Reagent tube 240 x 20 mm
88400-0452		Quartz tube

RESISTANCE FURNACE

089330034		Screw M4 x 20
09090		Reagent tube 32 x 280 mm
11170		Фильтр тонкой очистки
36720-2001		PTFE tube
70150		O-ring 6 x 2.5 mm

70320		O-ring 20 x 5 mm
73030		Viton tube 4 x 1
36000-3014		Ceran plate
36000-8000		Heating elements incl. contacting
36101		Стопор для лодочек
36216-2001		Combustion boat insertion stick, 1 piece (only for CS-d)
36218-2001		Combustion boat removing stick, 1 piece (only for CS-d)
36620-2001		Dust housing complete
36665		Spring
66100-0329		Screw
66300-0465		Thermostat
70380		O-ring 35 x 5 mm
70410		O-ring 48 x 3 mm, Viton
77505		Ceramic distance holder for heating elements
90162		Combustion tube 35 x 28 x 550 mm